

## Features

- + 10.1-inch IPS Screen with Built-in Record, Quad View Touch Screen,
- + Built-in 2.4G Wireless Receiver with Auto Pairing.
- + 1080P Digital Wireless 30 x Zoom Camera.
- + Lithium Polymer Magnetic Battery Pack 9600mAh or 25000mAh (Optional)
- + Night Vision Built-in 4 high-power infrared lights.
- + Built-in Reverse Polarity, LED Constant Current, Voltage Suppression Protection.
- + AI Pedestrian Detection (Option)
- + Stainless Steel Self Levelling Camera Bracket



QUAD Touch Screen Monitor Built-in Record



### Monitor 1080P 10.1" Wireless QUAD View Touch Screen Monitor (Model: 10QMHTWP)

Colour LCD Display	10.1 inch IPS Screen Waterproof Monitor ,
Wireless Receiver	Built-in 2.4G Wireless Receiver
Picture Mode	Single screen / dual screen/Three-screen/four-screen
Working Frequency	2400 ~ 2483.5MHZ
Recording Function	Maximum support 128GB SD card
Recording File	MP4 format
Receiving Sensitivity	≤-86 dB
Receiving Distance	Open ≤200m
Frequency Hopping Channel	80
Resolution	1024(H) X 600(V)dot
Colour System	PAL/NTSC (AUTO)
Brightness (cd/m2)	600
Load dump	ISO16750-2 Standard
Vibration Resistance	5G (conforms to GB-T2423056-2006 standard)
Operating Temperature	-20°C ~ 70°C
Operating Voltage	DC8-32V

### Camera 1080P Digital Wireless 30x Zoom (Model: CWZMS)

Image Sensor	1/2.8Color DSP / Resolution1080P
Wireless transmission	Built-in 2.4G digital wireless transmitter
Transmit Power	18dBm
Launch Distance	open ≤100 meters
Effective Pixels	1920(H) X1080(V)
Optical Zoom	30x
Focal Length	5.35 ~ 96.3mm
Aperture Value	F1.6 ~ F3.5
Horizontal Viewing Angle	64.1~3.6 Degrees (Wide Angle-Telephoto )
Visual Distance	5-200 meters
Zoom Speed	about 3 seconds (optical, wide-angle-telephoto)
Focus Mode	Auto focus
Day And Night Mode	IR-CUT automatic switching, Colour Daytime, B/W at Night
Infrared Distance	50 meters (built-in 4 high-power infrared lights)
Housing Material	Alloy Aluminium Housing with Stainless Steel Bracket
Waterproof Rating	IP69K
Operating Voltage	DC12-24V
Operating Temperature	-20°C ~ 60°C
Vibration Resistance	5G (conforms to GB-T2423056-2006 standard)
Dimensions	L 220 H x 90 x D 90 mm

### Rechargeable Magnetic Battery Pack ( Option ) Model RG96 or RG25

Battery Capacity	9600 or 25000mAh (Optional)
Charging Voltage	DC 5~14V
Charge Time	9.5H ( DC12V at 25°C, 15H ( DC 5V at 25°C,
DC Output	DC12V/0.8A (DC5.5/2.1 male)
Charging Cycle Temperature	0°~+45°
Discharge Locking Temperature	-20°~+60°
Magnetic Base	Magnetic Base
Waterproof Rating	IP66K
Anti-Vibration Rating	5G
Dimensions	L120 x H 79.5 x D 61mm



Rechargeable Magnetic Battery Packs (Option )      Power Cable 5.5 Meters (Option)



Model RBP



Model LRBP



Model SSC-5.5

### Flexible Zooming Method

Can control zoom-in/out and switch between manual/automatic zooming through a foot switch, Improving camera working efficiency.  
Option: Foot Switch (Model: FSP)